



Mattador™ Solid Core Door Product Information Sheet

Mattson Joinery is pleased to announce the availability of the **Mattador™** range of Solid Core Interior Grade Door Leaves.

These solid core door leaves are becoming a popular choice, as an **added security feature** in homes/apartments for bedroom and internal garage entry door applications.

These door leaves can be upgraded to **Certified Smoke Doors**, when hung in timber frames. Timber door stop/seal kit available.

These doors are, virtually **indestructible**.

Features and benefits:

- The **Mattador™** Solid Core Door Leaf is the **lightest** and one of the **strongest** wood based, solid core door materials currently available in New Zealand and Australia.
- The **Mattador™** is the first **E0** formaldehyde rated solid core door manufactured in New Zealand or Australia.
- The **Mattador™** offers superior **impact** strength and enhanced **security** features when compared to hollow core, and other timber based or infill solid core doors.
- The **Mattador™** is manufactured in New Zealand from **FSC Certified** plantation forestry wood products. These door leaves are environmentally friendly, (green).
- The **Mattador™** is available in (PQ) paint quality, machined with vertical or horizontal vee grooves, or can be supplied with veneer overlays.
- The **Mattador™** is available with vision panels, as required.
- The **Mattador™** can be factory cropped for mortice locks, as required.
- The **Mattador™** is suitable as replacement doors or can be supplied prehung in timber frames to suit the end - use application.
- The **Mattador™** door leaves can be recut, re-clashed, or edge filled (clashless) to suit any door size.

Sizes and Weights;

Available in 36 and 40mm thickness's, unprimed or primed, clashed or clashless , both vertical edges, **Mattador™** Solid Core Doors are available in the following range of standard leaf sizes and weights;

	36mm door leaf	40mm door leaf
• 1980 x <610mm	22.5 (kg)	24.9 (kg)
• 1980 x 710 / 760 / 810mm	26.1 / 27.9 / 29.7 (kg)	28.9 / 31.0 / 33.0 (kg)
• 1980 x 860 / 910mm	31.6 / 33.4 (kg)	35.0 / 37.1 (kg)

Miscellaneous:

- Over height doors <2500mm available upon request.
- Use 50mm minimum length x 8 gauge posi-drive c/s screws for hanging door leaves.
- Unprimed doors must be kept dry and fully undercoated upon arrival on site.
- Doors must be stored horizontally on a level surface, using three same size bearers.

Available from,



April 2009